

# Our Technology - Your Advantage

## Individual production according to your requirements

**Our standard range of laboratory coolers includes over 40 models. These chillers, commonly referred to as KÜHLMOBIL, have cooling capacities between 180 watts and 40 kW.**

But there are many more variations available with higher cooling capacities, almost all of these can be classified according to the following characteristics:

- Chiller with a compressor and air-cooled active cooling (waste-air will enter the ambient room)
- Chiller with a compressor and water-cooled active cooling (no waste-air to the ambient room)
- Water-Water chiller (system separator) without active cooling (up to 150 kW)
- Flow through chiller without a tank
- Chiller cooled with a fan only
- Combination appliances, of a chiller with a compressor air-cooled and also water-cooled in the same device; 2 in 1
- Chiller with a compressor and air-cooled active cooling as split version, part inside and part outside the room (no waste-air or noise to the ambient room)
- Air-cooled, water-cooled chillers or water-water chillers (system separators) without active cooling, for use with distilled water. The water side is constructed from V2A stainless steel and synthetic material.
- Air-cooled, water-cooled chillers or water-water chillers (system separators) without active cooling, for use with distilled water with constant conductance via an extra ion exchanger with it's own circuit. The water side is constructed from V2A stainless steel and synthetic material.
- Combination appliances of a chiller with a compressor air-cooled and also as water-water cooled in the same device; 2 in 1
- Flow through chiller with pump for cooling external open tanks or for example trout pools
- Closed cooling systems, instead of half open systems
- Cooling solutions in a special case for placements inside floor spaces
- Air-cooled chillers, for use outdoors
- Special chiller with special options as an air-cooled or water-cooled version

This product range is complemented by a wide selection of options, variations and recommended accessories, e.g. PVC tubing, remote control, bypass, multiple distributor, etc.

From all these possibilities, we configure exactly the device that suits your individual application.

Contact us!

